


**Features**

- Weatherproof IR Camera
- SONY/SHARP Color CCD
- IR LED:  $\phi 5 \times 30$ PCS ,IR Distance: 25M
- Water Resistance : IP66
- Cable built-in bracket
- Lens: Board Lens 3.6mm/F2.0
- Dimension :162(W) x72(H) x69(D)mm


**Specification**

Model	NIC30SHL	NIC30SHQ	NIC30SL	NIC30S	NIC30HF
Image Sensor	1/3"SONY			1/3"SONY	1/4"SHARP
Horizontal Resolution	540TV Line Low Illumination	540TV Line	420TV Line Low Illumination	420TV Line	
Pixels	PAL: 795 (H)× 596(V) NTSC: 811 (H)×508 (V)		PAL:500(H)×582(V) NTSC:510(H)×492(V)		
TV System	PAL/NTSC				
IR LED	$\phi 5 \times 30$ PCS				
IR Series Distance	25 M				
Lens	Board Lens 3.6mm/F2.0				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
Usable Illumination	0 Lux/F2.0 (LED ON)				
IR Power On	CDS Auto Control				
S/N Ratio	$\geq 48$ dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	$-10^{\circ}\text{C} \sim +50^{\circ}\text{C}$ RH95% Max				
Storage Temperature	$-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$ RH95% Max				
White Balance	Auto				
Power Source	DC12V 350mA				
Dimension	162(W) x72(H) x69(D)mm				
Weight	850g				