



Features

Weatherproof IR Camera

SONY/SHARP Color CCD

IR LED: $\phi 5 \times 24$ PCS ,IR Distance:20M

Water Resistance : IP66

3 Axis Bracket

Lens: Board Lens 3.6mm/F2.0

Dimension :175(W) x124(H) x83(D)mm



Specification

Model	NICG24SHL	NICG24SHQ	NICG24SL	NICG24S	NICG24HF
Image Sensor	1/3"SONY			1/3"SONY	1/4"SHARP
Horizontal Resolution	540TV Line Low Illumination	540TV Line	420TV Line Low Illumination	420TV Line	
Pixels	PAL: 795 (H)× 596(V) NTSC: 811 (H)×508 (V)		PAL:500(H)×582(V) NTSC:510(H)×492(V)		
TV System	PAL/NTSC				
IR LED	ø5 X 24 PCS				
IR Series Distance	20 M				
Lens	Board Lens 3.6mm/F2.0				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
Usable Illumination	0 Lux/F2.0 (LED ON)				
IR Power On	CDS Auto Control				
S/N Ratio	≥48dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10℃ ~ +50℃ RH95% Max				
Storage Temperature	-20℃ ~ +60℃ RH95% Max				
White Balance	Auto				
Power Source	DC12V 300mA				
Dimension	175(W) x124(H) x83(D)mm				
Weight	900g				