


Features

- Vandalproof IR Dome Camera
- SONY/SHARP Color CCD
- Usable Illumination: 0Lux(Built In IR LED ON)
- IR Distance: 20M
- IR LED: ϕ 5X24PCS
- Back Light Compensation(BLC)
- Lens: Board Lens 3.6mm/F2.0
- Dimension : ϕ 94 x 69(H) mm


Specification

Model	NIRDBSHL	NIRDBSHQ	NIRDBSL	NIRDBPC	NIRDBS	NIRDBHF
Image Sensor	1/3"SONY		1/3"SONY	1/4"PLXEL	1/3"SONY	1/4"SHARP
Horizontal Resolution	540TV Lines Low Illumination	540TV Lines	420TV Lines Low Illumination	480TV Lines	420 TV Line	
Pixels	PAL:795 (H)× 596(V) NTSC :811 (H) ×508 (V)		PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:752(H)×582(V) NTSC:768(H)×494(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)	
TV System	PAL/NTSC					
IR LED	ϕ 5 X 24PCS					
IR Series Distance	20 M					
Lens	Board Lens 3.6mm/F2.0(Optional)					
Sync System	Internal					
Usable Illumination	0.001 Lux/ F2.0 (LED ON)	0 Lux/F2.0 (LED ON)	0 Lux/F2.0 (LED ON)			
S/N Ratio	\geq 48dB (AGC OFF)					
Gamma Correction	0.45					
Video Out	Composite Signal (1.0Vp-p, 75 Ω)					
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec					
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec					
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max					
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max					
White Balance	Auto					
Power Source	DC12V 300mA					
Dimension	ϕ 94 x 69(H) mm					
Weight	450g					