

NV-8016F



Features

Stand-Alone DVR, H.264 Compression

High quality video Display: NTSC (720x480), PAL (704x576) real time display

Multiple Recording/ Search Categories: Date/Time, Event, Manual, Schedulenalarm, motion detection

Real time recording support: 480 Fps for NTSC at CIF image (400 Fps for PAL)

16ch Video recording at the same time

Preview resolution: 704 x 576 (PAL) , 720 x 480 (NTSC); Playback resolution: 16 x CIF

Pentaplex: Live, Record, Playback, Back-up and Network at the same time Backup: CD-RW (Option: DVD-RW), USB 2.0 and NET backup supported

PTZ camera control in local and remote area

Network Viewer

Static, Dynamic IP and DDNS, Support Internet Explorer and special client software Remote Live Monitoring, file searching, Backup, Playback and PTZ camera control Remote Configuration, Firmware Upgrade and Event (Alarm, Motion) Notification

Specification

Model	NV-8016F
Compression Format	H.264
Resolution	Preview resolution: 704 x 576 (PAL) , 720 x 480 (NTSC) Playback resolution: 4 x CIF Frames: $1F/S \sim 30F/S$ (Adjustable)
Hard Disk	2 SATA Hard Disk interface (Support Capacity from 40G to 4TB in Total)
Video Input	16 channel, BNC , $1.0V$ p-p/ 75Ω
Composite Video Output	1 channel, BNC, 1.0V p-p/75Ω
Monitor Video Output	NO
VGA Interface	1 VGA, Resolution: 800x600/60HZ, 1024x768/60HZ
Audio Input	NO
Audio Output	NO
Alarm Input	16 Channel, Trigger closed without Voltage, Open or Closed
Alarm Output	4 Channel, Trigger closed without Voltage, Open or Closed
Alarm Mode	Sensor Input, Motion Detection, Video Loss, Full Disk Space
Network	Ethernet (10/100M), LAN, WAN and ADSL
Control Way	USB2.0 Mouse, Remote Control, PTZ, Camera, RS485 x 1
Backup	USB2.0, CDRW, DVDRW and Network
Bit Rate	5 Levels: 120MB/H, 150MB/H, 250MB/H, 300MB/H, 500MB/H, 1~1000MB/H Self-defined
Password	Encrypted by 128-bit Numerical Digits with 2-Level Password Protection
Power Supply	220V(±10%)/50HZ, 180W
Consumption	50W (Without HDD)
Working Environment	Temperature: +5°C~+50°C; Humid: < 90%
Device Dimension	435mm×365mm×65mm
Weight	8kg

